

MR16

Halogen Lamps



Features and Benefits

- 4,000 to 6,000-hour life
- Whiter light
- Dimmable
- Energy efficient

Applications

- Grocery stores
- Retail stores
- Jewelers
- Office interiors
- Optical shops
- Restaurants
- Night clubs
- Landscape lighting
- Museums

There is an MR16 halogen lamp to fit almost any need

- The Econo MR16 lamps are a standard, affordable lighting choice.
- The Xtreme White™ MR16 offers brighter, whiter light.
- The Frost PAR™ MR16 spreads out light, keeping hot spots off display items.
- The Sure-Beam™ MR16 is designed to release 85% of the heat out of the back of the lamp, reducing heat on the display area.
- The Mirro™ Aluminum-Reflector MR16 lamp reflects light and heat downward, protecting the transformer and extending life.
- The Spectrachrome™ colored MR16 lamps are available in four colors.

LITETRONICS®

4101 West 123rd Street
Alsip, Illinois 60803
www.Litetronics.com

MR16 Halogen Lamps



MR16

SURE-BEAM™ Coolray Dichroic Reflector

LAMP	WATTS	BASE	VOLTS	DESCRIPTION	BEAM SPREAD	ORDERING CODE	QTY/ CASE	AVERAGE RATED LIFE	CORRELATED COLOR TEMP(K)	C.B.C.P.*	M.O.L.**
MR16	20	BI PIN	12	20 BAB MR16 FL	FLOOD	L-3819	10	6,000	3000	500	1.77"
	20	BI PIN	12	20 BAB MR16 FL CG	FLOOD	L-3827	10	6,000	3000	500	1.77"
	50	BI PIN	12	50 EXT MR16 SP	SPOT	L-3820	10	6,000	3050	10,200	1.77"
	50	BI PIN	12	50 EXZ MR16 NFL	NARROW FLOOD	L-3821	10	6,000	3050	3,100	1.77"
	50	BI PIN	12	50 EXN MR16 FL	FLOOD	L-3822	10	6,000	3050	1,850	1.77"
	50	BI PIN	12	50 EXN MR16 FL CG	FLOOD	L-3823	10	6,000	3050	1,850	1.77"
	50	BI PIN	12	50 FNV MR16 WFL CG	WIDE FLOOD	L-3829	10	6,000	3050	1,200	1.77"

MIRRO™ Aluminum-Reflector

LAMP	WATTS	BASE	VOLTS	DESCRIPTION	BEAM SPREAD	ORDERING CODE	QTY/ CASE	AVERAGE RATED LIFE	CORRELATED COLOR TEMP(K)	C.B.C.P.*	M.O.L.**
MR16	35	BI PIN	12	35 FMW/A MR16 FLM	FLOOD	L-3811	10	6,000	2900	1,350	1.77"
	50	BI PIN	12	50 EXN/A MR16 FLM	FLOOD	L-3812	10	6,000	2900	1,900	1.77"
	50	BI PIN	12	50 EXN/A MR16 FLM CG	FLOOD	L-3805	10	6,000	2900	2,900	1,900

SPECTRACHROME™ Color

LAMP	WATTS	BASE	VOLTS	DESCRIPTION	BEAM SPREAD	ORDERING CODE	QTY/ CASE	AVERAGE RATED LIFE	M.O.L.**
MR16	50	BI PIN	12	50 MR16 FL RED	FLOOD	L-3821R	10	6,000	1.77"
	50	BI PIN	12	50 MR16 FL GREEN	FLOOD	L-3821G	10	6,000	1.77"
	50	BI PIN	12	50 MR16 FL BLUE	FLOOD	L-3821B	10	6,000	1.77"
	50	BI PIN	12	50 MR16 FL AMBER	FLOOD	L-3821A	10	6,000	1.77"

ECONO MR 16 Lamps

LAMP	WATTS	BASE	VOLTS	DESCRIPTION	BEAM SPREAD	ORDERING CODE	QTY/ CASE	AVERAGE RATED LIFE	M.O.L.**
MR16	20	BI PIN	12	20 MR16 BAB FL CG	FLOOD	L-3800	10	4,000	1.77"
	20	BI PIN	12	20 MR16 BAB FL	FLOOD	L-3865	10	4,000	1.77"
	20	BI PIN	12	20 MR16 ESX SP	SPOT	L-3861	10	4,000	1.77"
	35	BI PIN	12	35 MR16 FMW FL CG	FLOOD	L-3801	10	4,000	1.77"
	35	BI PIN	12	35 MR16 FMW FL	FLOOD	L-3875	10	4,000	1.77"
	50	BI PIN	12	50 MR16 EXT SP	SPOT	L-3881	10	4,000	1.77"
	50	BI PIN	12	50 MR16 EXZ NFL	NARROW FLOOD	L-3883	10	4,000	1.77"
	50	BI PIN	12	50 MR16 EXN FL CG	FLOOD	L-3802	10	4,000	1.77"
	50	BI PIN	12	50 MR16 EXN FL	FLOOD	L-3885	10	4,000	1.77"

* Center Beam Candle Power

** Maximum Overall Length (in inches)

Please see the LITETRONICS CATALOG for more MR16 products.

