

## MICRO BRITE™

Cold Cathode Fluorescent Reflector Lamps



BR30 R20

### Features and Benefits

- 18,000 to 25,000-hour life
- Up to 85% energy savings compared to incandescent
- Dimmable (5-watt and 8-watt)
- Flashable (5-watt)
- Attractive designs, fits in standard fixtures
- Reduces replacement and maintenance costs
- Can be used indoors or outdoors
- 2-year warranty

### Applications

- General lighting
- Recessed cans
- Track lighting
- Sign applications
- Architectural perimeter lighting
- Exterior cove and accent lighting

### Micro-Brite Reflectors - Efficient, Long-Lasting, and Versatile

Micro-Brite™ cold cathode fluorescent lamps from Litetronics are a direct replacement for incandescent lighting. Micro-Brite lamps have an expected life of up to 25,000 hours and can save up to 85% in energy savings when compared to incandescent lamps. Due to their extremely long life, Micro-Brite lamps also reduce maintenance costs.

The R20 and BR30 Micro-Brite reflector lamps are efficient, long-lasting light sources. They are both dimmable, and the 5-watt R20 is also flashable. With Micro-Brite's immediate start, the flashable R20 can be used in message centers without blurring or trailing. Both lamps can be used indoors and outdoors in extreme conditions, and they have attractive designs that fit in standard fixtures. Get attractive lighting that lasts with Micro-Brite reflector lamps.

**LITETRONICS®**

4101 West 123rd Street  
Alsip, Illinois 60803  
[www.Litetronics.com](http://www.Litetronics.com)

# MICRO BRITE™ Cold Cathode Micro Compact Fluorescent Lamps



R20



BR30

LAMP	WATTS	BASE	VOLTS	DESCRIPTION	ORDERING CODE	QTY/ CASE	AVERAGE RATED LIFE	CRI	CORRELATED COLOR TEMP(K)	INITIAL LUMENS	M.O.L.**
R20	5 \$	MED LO	120	5W R20 FF LW	MB-509DL	15	25,000	82	2250	200	4.05"
	5 \$	MED LO	120	5W R20 FF PW	MB-509DP	15	25,000	82	2850	200	4.05"
	8 \$	MED	120	8W R20 FF PW	MB-809DP	15	18,000	82	2850	325	4.65"
BR30	8 \$	MED LO	120	8W BR30 FF LW	MB-900DL	6	18,000	82	2250	325	5.39"
	8 \$	MED LO	120	8W BR30 FF PW	MB-900DP	6	18,000	82	2850	325	5.39"

## SPECIFICATIONS

INPUT LINE FREQUENCY	50/60 HZ
RELIABLE OPERATING TEMP.	5°F – 105°F
POWER FACTOR	> .90
TOTAL HARMONIC DISTORTION	< .30

## CONVERSION CHART

CFL	=	INCANDESCENT
5-watt	=	30-watt
8-watt	=	45-watt

\$ Energy Savings

\*\* Maximum Overall Length (in inches)

