

SPIRAL-PAR™

Low-Profile Compact Fluorescent Lamps

Features and Benefits

- 8,000-hour life
- Energy Star qualified
- Up to 80% energy savings compared to incandescent
- Reduces labor costs
- Spiral reflector allows higher lumens per watt
- Direct replacement for incandescent PAR lamp
- Operates at a lower temperature than halogen PARs, reducing HVAC costs
- 1-year warranty

Litetronics Spiral PAR Fluorescent Lamp - Long Life Never Looked So Good!

Litetronics Spiral PAR™ compact fluorescent lamps allow users to save time and money, while maintaining attractive design and performance. They are as versatile as standard 50 to 120-watt incandescent PAR lamps, and they last four times as long. Spiral PAR lamps are effective for both indoor and outdoor applications, including track lighting and recessed cans.

Available in 2700K, 3500K, and 4100K, Litetronics SPLP PAR lamps are ideal for displaying vivid colors. In addition, the spiral reflector allows more lumens per watt than ordinary fluorescents. Replace your incandescent PARs with Litetronics Spiral PAR lamps, and start saving money today!



PAR 20

PAR 30

PAR 38

Applications

- Track lighting
- Recessed cans
- Indoor or outdoor use

LITETRONICS®

4101 West 123rd Street
Alsip, Illinois 60803
www.Litetronics.com

SPIRAL-PAR™ LOW PROFILE Compact Fluorescent Lamps



PAR20



PAR30



PAR38

| LAMP | WATTS | BASE | VOLTS | DESCRIPTION | ORDERING CODE | QTY/ CASE | AVERAGE RATED LIFE | CRI | CORRELATED COLOR TEMP(K) | INITIAL LUMENS | M.O.L.** |
|-------|-------|--------|-------|-------------------|---------------|-----------|--------------------|-----|--------------------------|----------------|----------|
| PAR20 | 9 \$ | MED | 120 | 9W SPLP PAR20 27 | L-1471 | 15 | 8,000 | 82 | 2700 | 300 | 3.82" |
| | 9 \$ | MED | 120 | 9W SPLP PAR20 35 | L-1475 | 15 | 8,000 | 82 | 3500 | 300 | 3.82" |
| | 9 \$ | MED | 120 | 9W SPLP PAR20 41 | L-1472 | 15 | 8,000 | 82 | 4100 | 300 | 3.82" |
| PAR30 | 15 \$ | MED LO | 120 | 15W SPLP PAR30 27 | L-1371 | 10 | 8,000 | 82 | 2700 | 725 | 5.15" |
| | 15 \$ | MED LO | 120 | 15W SPLP PAR30 35 | L-1375 | 10 | 8,000 | 82 | 3500 | 725 | 5.15" |
| | 15 \$ | MED LO | 120 | 15W SPLP PAR30 41 | L-1372 | 10 | 8,000 | 82 | 4100 | 725 | 5.15" |
| PAR38 | 20 \$ | MED LO | 120 | 20W SPLP PAR38 27 | L-1271 | 10 | 8,000 | 82 | 2700 | 975 | 5.55" |
| | 20 \$ | MED LO | 120 | 20W SPLP PAR38 35 | L-1275 | 10 | 8,000 | 82 | 3500 | 975 | 5.55" |
| | 20 \$ | MED LO | 120 | 20W SPLP PAR38 41 | L-1272 | 10 | 8,000 | 82 | 4100 | 975 | 5.55" |
| | 23 \$ | MED | 120 | 23W SPLP PAR38 27 | L-1571 | 15 | 8,000 | 82 | 2700 | 1,350 | 5.51" |
| | 23 \$ | MED | 120 | 23W SPLP PAR38 35 | L-1575 | 15 | 8,000 | 82 | 3500 | 1,200 | 5.51" |
| | 23 \$ | MED | 120 | 23W SPLP PAR38 41 | L-1572 | 15 | 8,000 | 82 | 4100 | 1,200 | 5.51" |

SPECIFICATIONS

| | |
|--------------------------|-------------|
| INPUT LINE FREQUENCY | 50/60 HZ |
| RELIABLE OPERATING TEMP. | 5°F – 105°F |
| POWER FACTOR | > .50 |

CONVERSION CHART

| CFL | = | INCANDESCENT |
|---------|---|--------------|
| 9-watt | = | 50-watt |
| 15-watt | = | 75-watt |
| 20-watt | = | 100-watt |
| 23-watt | = | 120-watt |

 Energy Star qualified

\$ Energy Savings

** Maximum Overall Length (in inches)

