

XTRA-LIFE™

Halogen Lamps



PAR30

PAR38

PAR30LN

PAR20

Features and Benefits

- 5,000 to 10,000-hour life
- Replaces higher wattage incandescent lamps
- Brighter, whiter light than 130V halogen PARs
- Reduces labor costs
- Brass base

Applications

- Recessed cans
- Down lights
- Track lighting
- Open fixtures
- Office buildings
- Hospitals
- Restaurants
- Retail Stores
- Shopping malls
- Banks

Xtra-Life — A Complete Line of Brighter, Longer Lasting Halogen Lamps

Litetronics International, Inc. uses top-grade materials and an intensive engineering process in manufacturing the Xtra-Life™ family of halogen lamps. This allows Xtra-Life lamps to last for 5,000 hours — twice as long as standard halogen lamps. Xtra-Life lamps have a brighter, whiter light than incandescent PARs. In addition, Xtra-Life lamps do not experience decreased lumen output over time.

The long life of sturdy Xtra-Life lamps helps save on maintenance and lamp replacement. The lamps also offer a significant energy savings when used to replace higher wattage incandescent lamps. It is easy to save time, energy, and money with Xtra-Life halogen lamps.

LITETRONICS®

4101 West 123rd Street
Alsip, Illinois 60803
www.Litetronics.com

XTRA-LIFE™ Halogen Lamps



PAR20



PAR30



PAR30LN



PAR38

LAMP	WATTS	BASE	VOLTS	DESCRIPTION	BEAM SPREAD	ORDERING CODE	QTY/ CASE	AVERAGE RATED LIFE	LUMENS	C.B.C.P.*	M.O.L.**
PAR20	35	MED	120-125	• 35 PAR20 FL	FLOOD	G-4510	15	5,000	310	750	3.15"
	50	MED	120-125	• 50 PAR20 SP	SPOT	G-4513	15	5,000	500	5,400	3.15"
	50	MED	120-125	• 50 PAR20 FL	FLOOD	G-4512	15	5,000	500	1,400	3.15"
	75	MED	120-125	• 75 PAR20 FL	FLOOD	G-4516	15	5,000	825	3,000	3.15"
PAR30	50	MED	120-125	• 50 PAR30 SP	SPOT	G-4551	15	5,000	580	11,050	3.54"
	50	MED	120-125	• 50 PAR30 FL	FLOOD	G-4549	15	5,000	580	1,150	3.54"
	60	MED	120-125	• 60 PAR30 FL	FLOOD	G-4557	15	5,000	750	1,500	3.54"
	75	MED	120-125	• 75 PAR30 SP	SPOT	G-4455	15	5,000	990	16,300	3.54"
	75	MED	120-125	• 75 PAR30 FL	FLOOD	G-4454	15	5,000	990	2,300	3.54"
	78	MED	130	• 78 PAR30 FL	FLOOD	G-4460	15	10,000~	1,100	2,400	3.54"
PAR30LN	50	MED	120-125	• 50 LN PAR30 SP	SPOT	G-4551LN	15	5,000	560	10,000	4.68"
	50	MED	120-125	• 50 LN PAR30 FL	FLOOD	G-4549LN	15	5,000	560	1,080	4.68"
	60	MED	120-125	• 60 LN PAR30 FL	FLOOD	G-4557LN	15	5,000	700	1,430	4.68"
	75	MED	120-125	• 75 LN PAR30 SP	SPOT	G-4455LN	15	5,000	950	14,400	4.68"
	75	MED	120-125	• 75 LN PAR30 FL	FLOOD	G-4454LN	15	5,000	950	2,150	4.68"
	78	MED	130	• 78 LN PAR30 FL	FLOOD	G-4460LN	15	10,000~	1,000	2,300	4.68"
PAR38	50	MED	120-125	• 50 PAR38 FL	FLOOD	G-4554	15	5,000	530	1,800	5.19"
	60	MED	120-125	• 60 PAR38 FL	FLOOD	G-4560	15	5,000	700	3,400	5.19"
	75	MED	120-125	• 75 PAR38 SP	SPOT	G-4201	15	5,000	940	16,000	5.19"
	75	MED	120-125	• 75 PAR38 FL	FLOOD	G-4200	15	5,000	940	3,800	5.19"
	75	MED	120-125	• 75 PAR38 WFL	WIDE FLOOD	G-4203	15	5,000	940	1,050	5.19"
	78	MED	130	• 78 PAR30 SP	SPOT	G-4077	15	10,000~	1,000	19,300	5.19"
	78	MED	130	• 78 PAR38 FL	FLOOD	G-4078	15	10,000~	1,000	4,000	5.19"
	85	MED	120-125	• 85 PAR38 FL	FLOOD	G-4082	15	5,000	1,200	5,000	5.19"

~10,000 hours when operated at 120 Volts

• LITETRONICS EXCLUSIVE

* Center Beam Candle Power

** Maximum Overall Length (in inches)

