



### Halogen Lamps



MR 16

PAR 30

PAR 38

PAR 30LN

PAR 20

#### Features and Benefits

- 3,000 to 4,000-hour life
- Emphasizes true colors and textures
- Eliminates color-mixing problems
- Neodymium-infused lens reduces yellow light, providing whiter light than standard halogen lamps

#### Applications

- Color-critical product displays
- Cosmetics
- Furniture
- Jewelry
- Paint and other wall coverings
- Carpets and rugs
- Crystal and china
- Artwork and artifacts
- Food products

#### Xtreme White Halogen PAR Lamps Bring Whiter Light, Truer Color

Xtreme White™ halogen PAR lamps have a proprietary lens that reduces yellow light. This gives Xtreme White lamps a 3500K light that is much closer to the appearance of sunlight compared to standard halogen lamps that typically offer 2900K light.

The difference is clear when people see how Xtreme White lamps bring out the true colors and textures of products. Xtreme White lamps improve the look of any display and are excellent for retail and color-sensitive applications. In areas that use both halogen and fluorescent lighting, the Xtreme White eliminates color-mixing problems and creates a uniformly lit environment.

Engineered with top-grade materials, Xtreme White lamps provide long-lasting halogen light. With a 3,000 to 4,000-hour average life, Xtreme White lamps last twice as long as most halogen lamps. For quality, long-lasting lamps that show merchandise in the best light, look no further than Xtreme White.

**LITETRONICS®**

4101 West 123rd Street  
Alsip, Illinois 60803  
[www.Litetronics.com](http://www.Litetronics.com)



# Xtreme<sup>™</sup> white Halogen Lamps



MR16



PAR20



PAR30



PAR30LN



PAR38

LAMP	WATTS	BASE	VOLTS	DESCRIPTION	BEAM SPREAD	ORDERING CODE	QTY/ CASE	AVERAGE RATED LIFE	CORRELATED COLOR TEMP (K)	M.O.L.**
MR16	50	BI PIN	12	• 50 EXN/A MR16 FLM CB 33 CG	FLOOD	L-3850	10	6,000	3500	1.77"
PAR20	50	MED	120-125	• 50 PAR20 FL XTREME WHITE	FLOOD	G-4800	15	4,000	3500	3.15"
PAR30	50	MED	120-125	• 50 PAR30 FL XTREME WHITE	FLOOD	G-4803	15	4,000	3500	3.54"
	75	MED	120-125	• 75 PAR30 SP XTREME WHITE	SPOT	G-4804	15	4,000	3500	3.54"
	75	MED	120-125	• 75 PAR30 FL XTREME WHITE	FLOOD	G-4805	15	4,000	3500	3.54"
PAR30LN	50	MED	120-125	• 50 LN PAR30 FL XTREME WHITE	FLOOD	G-4803LN	15	4,000	3500	4.68"
	75	MED	120-125	• 75 LN PAR30 FL XTREME WHITE	FLOOD	G-4805LN	15	4,000	3500	4.68"
PAR38	85	MED	120-125	• 85 PAR38 FL XTREME WHITE	FLOOD	G-4810	15	4,000	3500	5.19"
	85	MED	120-125	• 85 PAR38 SP XTREME WHITE	SPOT	G-4811	15	4,000	3500	5.19"
	105	MED	120-125	• 105 PAR38 FL XTREME WHITE	FLOOD	L-8801	15	3,000	3500	5.19"

• LITETRONICS EXCLUSIVE

\*\* Maximum Overall Length (in inches)

