

Rough Service[™] Incandescent Lamps

Features and Benefits

- 20,000-hour life
- Lasts up to 26 times longer than standard incandescents
- Reduced labor and replacement costs
- Triple alloy tungsten filament
- Seven-support filament mounting adds durability
- Three getters to neutralize impurities
- Brass base prevents corrosion
- 2-year warranty

Attractive, Decorative Lighting With Rough Service Lamps

Litetronics International, Inc. offers an entire line of Rough Service[™] incandescent lamps that have an average life of 20,000 hours. That is up to 26 times longer than standard incandescent lamps. Rough Service lamps maintain higher light output throughout the life of the lamp, while other incandescent lamps have up to 20% light loss.

The triple alloy tungsten filament helps Rough Service lamps achieve longer life with superior color and lumens, and the lamps' unprecedented three getters neutralize any impurities that could potentially shorten lamp life. A special seven-support filament mounting allows Rough Service lamps to function well anywhere — even in areas with high vibration.

The G25 and G40 Rough Service incandescent lamps can be used in any setting that calls for decorative globe lighting. These medium-base lamps are available in 25 and 40-watt models and reduce lamp replacement and maintenance costs — even when compared to other extended service lamps. The T6 lamp is an excellent choice for exit and stairway signs, picture lighting, or decorative applications. Attractive, long-life lighting is here with Rough Service decorative lamps.



T6

G25

G40

Applications

- Restaurants
- Bathroom vanities
- Decorative lighting
- Hotels
- Hallway lighting
- Exit and stairway signs (T6)
- Picture lights (T6)

LITETRONICS[®]

4101 West 123rd Street
Alsip, Illinois 60803
www.Litetronics.com

Rough Service™ Incandescent Lamps



T6



G25



G40

LAMP	WATTS	BASE	VOLTS	DESCRIPTION	FINISH	ORDERING CODE	QTY/ CASE	AVERAGE RATED LIFE	LUMENS	M.O.L.**
T6	10 \$	DCB	120	10 T6	CLEAR	L-233	60	20,000	30	4.25"
	10 \$	INT	120	10 T6	CLEAR	L-234	60	20,000	30	4.25"
	10 \$	CAND	120	10 T6	CLEAR	L-235	60	20,000	30	4.40"
G25	25	MED	120	25 G25 CL	CLEAR	L-215	60	20,000	190	4.48"
	25	MED	120	25 G25 WH	WHITE	L-218	60	20,000	190	4.48"
	40	MED	120	40 G25 CL	CLEAR	L-216	60	20,000	320	4.48"
	40	MED	120	40 G25 WH	WHITE	L-219	60	20,000	320	4.48"
G40	25	MED	120	25 G40 CL	CLEAR	L-199	24	20,000	190	6.92"
	40	MED	120	40 G40 CL	CLEAR	L-200	24	20,000	320	6.92"

\$ Energy Savings, 10-watt T6 lamp replaces a 20-watt T6 -1/2 exit lamp.

** Maximum Overall Length (in inches)