

SPIRAL-LITE™

Compact Fluorescent Lamps



R30

R40

PAR38

A19

Features and Benefits

- 8,000-hour life
- ENERGY STAR® qualified
- Up to 80% energy savings compared to incandescent
- Same familiar shapes as incandescent
- Fits standard fixtures
- 1-year warranty

Applications

- General lighting
- Table lamps
- Floor lamps
- Ceiling fixtures
- Recessed cans
- Track lighting
- Theatres
- Bathrooms
- Vanities

Spiral-Lite Covered CFLs Offer Attractive Savings in Familiar Shapes

Litetronics Spiral-Lite™ Covered CFLs come in a variety of familiar shapes to combine the energy savings of compact fluorescent lamps with the attractive look and feel of an incandescent. Available in A19, R30, R40, and PAR38, Spiral-Lite Covered CFLs provide up to 80% energy savings in a wide range of applications. These energy savings help lower utility bills and reduce greenhouse gas emissions.

Spiral-Lite Covered CFLs are ENERGY STAR® qualified and have an average life of 8,000 hours. This helps reduce replacement, labor, and maintenance costs. In addition to their familiar shapes, Spiral-Lite Covered CFLs have either 2700K color temperature that provides the same warm lighting as incandescent lamps or a cool white, 4100K color. Replace inefficient incandescent lamps while maintaining the same attractive look with Spiral-Lite Covered CFLs.

LITETRONICS®

6969 W. 73rd St.
Bedford Park, IL 60638
www.Litetronics.com

SPIRAL-LITE™ Compact Fluorescent Lamps

Covered



A19



R30



R40



PAR38

LAMP	WATTS	BASE	VOLTS	DESCRIPTION	ORDERING CODE	QTY/ CASE	AVERAGE RATED LIFE	CRI	CORRELATED COLOR TEMP(K)	INITIAL LUMENS	MEAN LUMENS	M.O.L.**
A19	14 \$	MED	120	14W A19 27	L-14527A19-1	50	8,000	82	2700	850	725	4.88"
R30	15 \$	MED	120	15W R30 27	L-15527R30-1	24	10,000	82	2700	750	675	5.47"
	15 \$	MED	120	15W R30 41	L-15541R30	24	10,000	82	4100	750	675	5.47"
R40	23 \$	MED	120	23W R40 27	L-23527R40	24	8,000	82	2700	1,300	1,175	6.34"
	23 \$	MED	120	23W R40 41	L-23541R40	24	10,000	82	4100	1,300	1,175	6.34"
PAR38	23 \$	MED	120	23W PAR38 27	L-23527P38	24	8,000	82	2700	1,300	1,175	6.34"
	23 \$	MED	120	23W PAR38 41	L-23541P38	24	10,000	82	4100	1,300	1,175	6.34"

SPECIFICATIONS

INPUT LINE FREQUENCY	50/60 HZ
RELIABLE OPERATING TEMP.	-5°F – 105°F
POWER FACTOR	> .50

CONVERSION CHART

CFL	=	INCANDESCENT
14-watt	=	60-watt
15-watt	=	65-watt
23-watt	=	120-watt

ENERGY STAR® Qualified

\$ Energy Savings

** Maximum Overall Length (in inches)

