

SPIRAL-PAR™

Low-Profile Compact Fluorescent Lamps



PAR 20



PAR 38

Features and Benefits

- 8,000-hour life
- ENERGY STAR® qualified
- Up to 80% energy savings compared to incandescent
- Reduces labor costs
- Spiral reflector allows high lumens per watt
- Direct replacement for incandescent and halogen PAR lamps
- Operates at a lower temperature than halogen PARs, reducing HVAC costs
- 1-year warranty

Applications

- Track lighting
- Recessed cans
- Indoor or outdoor use

Litetronics Spiral PAR Fluorescent Lamp - Long Life Never Looked So Good!

Litetronics Spiral PAR™ compact fluorescent lamps allow users to save time and money, while maintaining attractive design and performance. They are as versatile as standard 50 to 120-watt incandescent PAR lamps, and they last four times as long. Spiral PAR lamps are effective for both indoor and outdoor applications, including track lighting and recessed cans.

Available in 2700K, 3500K, and 4100K, Litetronics SPLP PAR lamps are ideal for displaying vivid colors. In addition, the spiral reflector allows more lumens per watt than ordinary fluorescents. Replace your incandescent PARs with Litetronics Spiral PAR lamps, and start saving money today!

LITETRONICS®

6969 W. 73rd St.
Bedford Park, IL 60638
www.Litetronics.com

SPIRAL-PAR™ LOW PROFILE Compact Fluorescent Lamps



PAR20



PAR38

LAMP	WATTS	BASE	VOLTS	DESCRIPTION	ORDERING CODE	QTY/CASE	AVERAGE RATED LIFE	CRI	CORRELATED COLOR TEMP(K)	INITIAL LUMENS	MEAN LUMENS	M.O.L.**
PAR20	9 \$	MED	120	9W SPLP PAR20 27	L-1471	15	8,000	82	2700	300	275	3.82"
	9 \$	MED	120	9W SPLP PAR20 41	L-1472	15	8,000	82	4100	300	275	3.82"
PAR38	23 \$	MED	120	23W SPLP PAR38 41	L-1572-1	15	10,000	82	4100	1,200	1,075	5.51"

SPECIFICATIONS

INPUT LINE FREQUENCY	50/60 HZ
RELIABLE OPERATING TEMP.	5°F – 105°F
POWER FACTOR	> .50

CONVERSION CHART

CFL	=	HALOGEN	=	INCANDESCENT
9-watt	=	35-watt	=	50-watt
23-watt	=	90-watt	=	120-watt

 ENERGY STAR® qualified

\$ Energy Savings

** Maximum Overall Length (in inches)

