


EXTENDER FOR VTCS SERIES

PLUGGABLE SENSOR (EJ50)

Can be used in conjunction with (SFSAS01)

Installation Instructions



WHAT COMES IN THE BOX


Extender

SAFETY INSTRUCTIONS AND WARNINGS



- When using electrical equipment, basic safety precautions should always be observed
- This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved
- Installation should only be conducted by a qualified electrician in accordance with NEC and any relevant local building codes.
- Be certain electrical power is OFF before and during installation and maintenance.
- To prevent wiring damage or abrasion, do not expose wiring to edges of sheet metal or sharp objects.

WIRING INSTRUCTIONS

1. Before installation, **always turn off the power supply from main circuit breaker first!**
2. Open the fixture, remove knockout.
3. Remove lock nut from 3-wire elbow (SFSAS01 - Sold Separately) and add to extender. Attach extender to knockout and tighten to fixture.
4. Follow wiring diagram for connections (Figure 1).
5. Close the fixture.
6. Turn on the power.



DIMENSIONS/SIZE



Unit: mm / Inches

Thank you for choosing

LITETRONICS®

6969 W. 73rd Street

Bedford Park, IL 60638

WWW.LITETRONICS.COM

CustomerService@Litetronics.com or 1-800-860-3392



The information and product specifications contained in these instructions are based upon data believed to be accurate at the time of printing. This information is subject to change without notice and without incurring liability. If you have questions regarding specific product details, please contact us at 800-860-3392 or via email at customerservice@litetronics.com. To check for an updated version of these instructions, please visit www.litetronics.com.