

# PLUG-IN BLUETOOTH PIR SENSOR WITH IR

PROJECT:		
CATALOG #		
TYPE:		DATE:



## DESCRIPTION

When utilized with select fixtures, the SC010 enables occupancy sensing and daylight harvesting. Settings can be easily adjusted via remote control (Part# SCR054).

This plug-in sensor is compatible with the Litetronic's low bay LED fixtures including panels, volumetrics, retrofit kits, and strip fixtures.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment

## \*RF warning for Mobile device:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

## APPLICATIONS

- Car dealership
- Schools, campuses, day care
- Commercial
- Retail
- Event Centers
- Schools, campuses
- Storage rental facilities
- Multi-family, apartment complex
- Healthcare Facilities
- Offices & Municipal Buildings

## FEATURES

- Plug-In
- -22°F to 131°F (-30°C to 55°C)
- Integrated Bluetooth Connectivity
- Daylight Harvesting
- Occupancy Sensing
- Low-profile Linear Design with Minimal Height above Luminaire

## ORDERING INFORMATION

Listed below are the max load based mains voltage.

ORDERING CODE	DESCRIPTION	BASE	VOLTS
SC010	PLUG-IN Bluetooth PIR SENSOR with IR	Plug-In	12V DC

## CERTIFICATIONS

